

## DVW-304N



- High Quality Real Time Display - Max. 120fps (NTSC) / 100fps (PAL)
- High Quality and High Speed Recording
- Watermark Function
- Remote Observation through Network
- User-Friendly Graphic Interface
- MPEG4 Compression
- 1, 4 Screen Division
- Emergency Screen Auto Transfer to Center Software

Display	Speed	NTSC: 120fps; PAL: 100fps
	Screen Division	1,4 Division
Recording	Max Speed (@ CF)	NTSC: 120fps; PAL: 100fps
	Resolution	NTSC: 704x480, 704x240, 352x240 PAL: 704x576, 704x288, 352x288
Video	Recording Option	Continuous, Motion, Sensor and Pre-Alarm
	Format	NTSC/PAL
	CODEC	MPEG4
	Input	4ch
	Output	7" Wide LCD (800x480), CVBS 1 Port (Quad)
Audio	Input	1ch (line input)
	Output	1ch
	CODEC	ADPCM
Alarm	Input	2 ports
	Output	2 ports
Network	Transmission	Ethernet (RJ45)
	Protocol	TCP/IP (support dynamic IP)
Backup	Device	USB, Network
	Remote Control	Remote Software (CMS)
Other Function	Remote Alarm	E-mail, CMS report
	PTZ	RS232C/485
	W/D Function	Yes
	Image Authentication	Watermark
	Language	10 Languages
	Password	Multi-Level User Password Authorization
	USB	1 Port (USB2.0)
Power Source	AC 12V, 50/60Hz (Adaptor Included)	
Dimensions	186mm(W) x 60mm(H) x 265mm(D)	
Weight (net)	1.5kg (5.94 lbs)	