

DVW-304T



- High Quality Real Time Display - Max. 120fps (NTSC) / 100fps (PAL)
- High Quality and High Speed Recording
- Watermark Function
- Remote Observation through Network
- User-Friendly Graphic Interface
- MPEG4 Compression
- 1, 4 Screen Division
- Emergency Screen Auto Transfer to Center Software

Display	Speed	NTSC: 120fps; PAL: 100fps
	Screen Division	1,4 Division
Recording	Max Speed (@ CF)	NTSC: 120fps; PAL: 100fps
	Resolution	NTSC: 704x480, 704x240, 352x240 PAL: 704x576, 704x288, 352x288
Video	Recording Option	Continuous, Motion, Sensor and Pre-Alarm
	Format	NTSC/PAL
	CODEC	MPEG4
	Input	4ch
Audio	Output	CVBS, Spot out (1ch quad), VGA, S-Video
	Input	4ch (line input)
	Output	1ch
Alarm	CODEC	ADPCM
	Input	4 ports
Network	Output	4 ports
	Transmission	Ethernet (RJ45)
Backup	Protocol	TCP/IP (support dynamic IP)
	Device	USB, Network
Other Function	Remote Control	Remote Software (CMS)
	Remote Alarm	E-mail, CMS report
	PTZ	RS232C/485
	W/D Function	Yes
	Image Authentication	Watermark
	Language	10 Languages
	Password	Multi-Level User Password Authorization
USB	3 Port (USB2.0)	
Power Source		AC100 ~ 240V, 50/60Hz
Dimensions		215mm(W) x 88mm(H) x 370mm(D)
Weight (net)		5kg (11 lbs)